- 14. 14. Water storage tanks shall be provided with mosquito proof lids and over flow pipes. The tanks should be provided with access ladders wherever necessary.
- 15. The drains surrounding the plot if any should be constructed with PCC and should be covered with removable RCC slabs of sufficient thickness.
- 16. The applicant should gift the road widening area to the council before applying for the Occupancy certificate, if the applicant has utilized the extra FAR in lieu of the road widening
- 17. The applicant should plaster and paint the building internally as well as externally before applying for Occupancy certificate. Exposed brick/laterite/concrete /stone / ashlars masonry finish to buildings will also be permitted.
- 18. The applicant should provide a dustbin at a convenient place accessible for the Municipal vehicle for collection of garbage.
- 19. Road widening area shall be asphalted to the existing road level before applying for occupancy certificate.
- 20. Garages and Parking areas shown in the approved plan shall be strictly used for parking purposes only and should be easily accessible to vehicles. No commercial activities shall be allowed in these areas.
- 21. Access up to the entrance of the building is to be paved and is provided with drainage facilities.
- 22. Space for parking of vehicles is clearly demarcated on the ground.
- 23. No Restaurants/Bars will be permitted in the shops unless a separate soak pit is provided besides confirming to the rules in force.
- 24. No commercial activities will be permitted in the shops unless a separate permission is obtained from this council.
- 25. All temporary sheds/existing buildings shown to be demolished in the plan are demolished before applying for Occupancy certificate.
- 26. Fire Escape staircases, if applicable shall be constructed as indicated in the approved plans.
- All internal courtyards should be provided with drainage outlet.
- 28. The applicant should maintain all existing natural drains in the plot and should not block them at any stage.
- 29. No soak pit or other structures should come in the road widening area.
- 30. The plot boundary should be cordoned off by continuous sheet fencing either of wood or metal during the construction period.
- 31. The construction of compound wall should not obstruct any pathway or any public access. The applicant shall make necessary arrangements for smooth flow of rain water by keeping adequate openings in the compound wall for the purpose.
- 32. No gates shall open outwards on to the road.
- 33. The construction of the compound wall should be as per the approved plan. The applicant shall inform this council after the completion of the compound wall.
- 34. Drinking water well should be 15 meters away from any soak pit.